



SEGMENTATI SALDATURA LASER

SEG. LASER WELDED / SEG. LASERGESCHWEIßT
SEG. SOUDURE LASER / SEG. SOLDADURA LÁSER



ASE D

APPLICAZIONE: ASFALTO.

APPLICATION: ASPHALT.

EINSATZBEREICH: ASPHALT.

APPLICATIONS: ASPHALTE.

APLICACIÓN: ASFALTO.

PER POTENZA FINO A 15 kW.


FOR POWER UP TO 15 kW.

FÜR BIS 15 kW LEISTUNG.

POUR PUISSANCE JUSQU'À 15 kW.

PARA POTENCIA HASTA 15 kW.

10



* 25,4 + PH



CODICE
CODE / KODE
CODE / CODIGO

Ø

mm

Z(a)



€

E77A300E	300N	2,8	18(3)	8024788008371	149,00
E77A350E	350N	3,0	21(3)	8024788008388	170,00
E77A400E	400N	3,2	24(4)	8024788008395	204,00
E77A450E	450N	3,6	27(4)	8024788008401	242,00
E77A500E	500N	3,6	30(5)	8024788008418	298,00
E77A600E	600N	4,2	36(6)	8024788008425	402,00



(a) SEGMENTI RINFORZATI INCLINATI per evitare l'usura dell'anima nella zona di saldatura.

REINFORCED SLOPING SEGMENTS to avoid the wear of the steel core in the weld area.

MIT SCHRÄGSCHUTZSEGMENTEN.

SEGMENTS INCLINES RENFORCES pour éviter l'usure de la tôle dans la zone de soudure.

SEGMENTOS INCLINADOS REFORZADOS para evitar el desgaste del soporte en la zona de soldadura.

* Foro diverso a richiesta.

Specify the diameter of the hole when you place the order. / Den Durchmesser der Bohrung im Auftragsstadium spezifizieren.
Préciser le diamètre du trou au moment de la commande. / Especificar el diámetro del eje al realizar el pedido.

S.5
CAP. 9

