

FG15 100-150

Compact and easy to handle, it is an ideal mix for limited working areas



TROLLEY FOR THE DRUM HANDLING
Helpful for the operations of discharge and movement of the material.

GEARED MOTOR IN OIL BATH
It grants an extreme silence.

MAGNETOTHERMIC SWITCH WITH LOW-VOLTAGE COIL IP55 AND PLUG IP67



EXTENSIBLE LEGS
They allow the regulation to of the loading height (max/min 650/430 mm).

PLANETARY MIXING SYSTEM WITH FORCED SPEED
It allows a homogeneous mix in reduced times (mix 60 lt of mortar in about 40" with FG1515MM).



SAFETY ELECTRIC DEVICE
Thanks to a limit stop, the rotation of the tools is blocked by lifting protection net (FG1510MM-FG1515MM).

IT ALLOWS TO MIX WITHOUT THE SUPPORT OF THE OPERATOR
It doesn't transmit harmful vibrations for health.

Technical features		FG15 100	FG15 150
Drum capacity	lt	100	150
Mix capacity	lt	60	80
Drum diameter	mm	700	705
Paddle rotations no.	rpm	32	32
Machine weight	kg	96	110
Single phase enging	Kw	0,6	0,75
Electrical input	A	6	7
Operator position Lp Db	A	68	68
Length	mm	925	880
Depth	mm	980	880
Height	mm	1520	1000